



CMX2402 Specification Sheet					
lte	em	UNITS		Details	REMARKS
ENIGINE					
Maximum Output		Kw(ps)	16.5(22.4)	Air cooled 4 cycle V twin gasoline engine	Net Value
Compression Ratio		-	9.3	Powerful due to new Cooling Design and High Precision	
Air Cleaner		-	Cyclone	Optimize for Dust	By Donaldson
Carburetor		Barrel	Double	Great Response due to Less Uneven Air Fuel Mixture	
Noise		db.	98.5	Less Noise	
MOWER	DECK				
Maximum cutting width		mm	975		
Cutting height adjustment		mm	0-150	Great Work for Unevenness Terrain as Avoiding Flying Stones	
Cutting blade		-	Free blade	Designed blade to cut weeds efficiently	
TRAVEL					
Drive system		-	AWD		
Traveling Speed		km/h	13.8	High Speed Gear	
Operating Speed		km/h	7.7	Low Speed Gear	
DIMENS					
Mass		kg	365		Without fuel
Overall length		mm	1,998	Overall Width 1085mm	
Overall width		mm	1,085		
Overall		mm	1,015	Overall Height 1015mm Freed Front B80mm Ground Clearance 125mm Ground Clearance 125mm	
Tread	Front wheel	mm	860		
	Rear wheel	mm	800		
Fuel tank		L	20		
Front wheel	Size			Suitable te verieue terrein	
	SIZE Straight diameter	-	4.00-7(2PR) 400	Suitable to various terrain	4
Rear wheel	Straight diameter	mm		Suitable to various terrain	
	Straight diameter	- mm	440		4
	Straight diameter	mm	440		

Specifications are subject to change. We will keep you informed if there is any changes on those specifications.