



MORBARK

Perfect for utility line clearing, residential tree services, rental yards and municipalities, this powerful and compact model is easy to maneuver. The **Eeger Beaver 1415** is also available with tracks for right of way clearing, highway clean-ups and hard to reach areas requiring a self-propelled unit for material access.

The direct driven dual feed wheel system with serrated teeth and knife bar combination and end cap ripper teeth allow positive material feeding and reduced material wrapping around the feed wheel shaft for increased feeding efficiency.

MADE FOR *MORE* TO KEEP PACE WITH *YOU*



**EGER
BEEVER**

1415

**BRUSH
CHIPPER**

FEATURES AND BENEFITS

- 360° manual crank swivel discharge with adjustable height puts chips right where they're needed without removing the Beaver from the tow vehicle.
- The powerful dual feed wheel system generates more than 3,300 lb/ft (4,474 Nm) of pulling force. The Hydra-Lift™ compression system with spring-assisted down pressure aids in feeding difficult limbs.
- Drive belt inspection cover provides easy access for drive system maintenance.
- The 31" high x 60" wide (78.7 x 152.4 cm) chute opening and 14" high x 15" wide (35.6 x 38.1 cm) throat opening allows for easy feeding of branchy material and reduced saw labor.



MORBARKDEALERS.COM



MORBARK

**EEGER
BEEVER**

1415 BRUSH CHIPPER SPECIFICATIONS

Specifications may vary with equipment options

Updated 4/19/19

GENERAL	US	METRIC
Height	8'5"	2.56 m
Width	5'11"	1.8 m
Length	15'5"	4.7 m
Gross weight (approximate)	5,500 lb	2,495 kg
Suspension	7,000 lb Torflex	3,175 kg Torflex
Infeed opening (height x width)	31" x 60"	78.7 x 152.4 cm
Throat opening (height x width)	14" x 15"	35.6 x 38.1 cm
Drum (width x diameter)	14.5" x 21.4"	36.8 x 54.3 cm
Engine	CAT, Perkins or PSI	
Horsepower	49–145 HP	36.5–108.1 kW
Fuel capacity	24.5 gallons	92.7 L
Hydraulic capacity	17 gallons	64.4 L
Frame	8.2 lb, 6" channel	3.7 kg, 15.2 cm channel
Tires	(2) 235/80R16	
Hitch	2.5" Pintle	6.4 cm Pintle

EQUIPMENT HIGHLIGHTS

- 14.5" (36.8 cm) wide x 21.4" (54.3 cm) diameter staggered-knife-pocket drum with two dual-edged chipper knives and dual-sided, chambered air impeller system
- Top and bottom horizontal feed wheels equipped with serrated teeth and knife bars
- Reversing automatic feed system
- Enclosed engine with gauge panel, radiator fines screen and slide rails for belt adjustment
- Fuel tank sight gauge, drain plug and shut-off valve
- Hydraulic tank shut-off valve, drain plug and clean-out cover
- Live hydraulics; ball valve, pump, motor and control valve
- 3" x 5" (12.7 x 7.6 cm) tubular steel telescoping drawbar with two 12" (30.5 cm) extensions

OPTIONS INCLUDE

- ChipSafe® Operator Safety Shield
- Folding Infeed Tray
- Winch Package: heavy-duty, 5,000 lb (2268 kg) pull capacity with rope and 10' (3 m) chafe guard
- Custom Paint and Logo Packages
- Bottom Bump Bar
- Hydraulic Swivel Discharge
- Cone Holder
- Flow Control
- Axle Options Available
- Spare Tire and Mount
- Strobe Light
- Pusher Paddle
- Infeed Curtain
- Rear Jacks

