

# SKID-STEER LOADER **S510**

Operating Weight2686 kgEngine Power36.5 kWRated Operating Capacity810 kg



## **S510 - SPECIFICATIONS**

1619 kg 810 kg 64.7 L/min 23.8-24.5 MPa 17.3 km/h 11.8 km/h

Diesel

Liquid

4

158.6 Nm

2433 cm<sup>3</sup>

93.7 L

2686 kg

2342 kg

Joystick Controls (SJC)

Lift arm support

Spark arrester

Back-up alarm

Manual

two fully reversing hydrostatic motors

Engine/hydraulics system shutdown

Automatically activated glow plugs

Cushioned lift and tilt cylinders

Kubota/V2403 (iT4)

36.5 kW (48.9 HP)

#### Performance

| Tipping load (ISO 14397-1)             |
|--|
| Rated operating capacity (ISO 14397-1) |
| Pump capacity                          |
| System relief at quick couplers        |
| Max. travel speed (high range-option)  |
| Max. travel speed (low range)          |
| Engine                                 |
| Make/Model                             |

#### Fuel Cooling Power at 2700 RPM (SAE J1995 Gross) Torque at 1600 RPM (SAE J1995 Gross) Number of cylinders Displacement Fuel tank

#### Weights Operating weight Shipping weight without bucket

Controls Vehicle steering Loader hydraulics tilt and lift

Front auxiliary (standard)

**Drive System** 

Transmission

Standard Features Bobcat Interlock Control System (BICS) Parking brake Operator cab1 dome light and electrical power port Operating lights, front and rear Standard seat Seat belt Seat bar 10x16.5, 10-ply, Heavy duty tyres Bob-Tach<sup>™</sup> frame 1. Roll Over Protective Structure (ROPS) - meets requirements of SAE-J1040 and ISO 3471; Falling Object Protective Structure (FOPS) - meets requirements of SAE-J1043 and ISO 3449, Level I

#### Options

Deluxe pressurized cab with heating Selectable Joystick Controls (SJC-R/C Ready) Cloth suspension seat 10x16.5, 10-ply, Heavy duty tyres, offset rims 10x16.5, 10-ply, Severe duty tyres 7-pin attachment control Noise reduction kit Deluxe instrument panel Keyless start with password capability Hydraulic bucket positioning (including ON/OFF switch)

2 speed Power Bob-Tach™ Radio Beacon Road option Automatic ride control Automatic reversing fan Custom paint color (min order of 5 units) Suspension seat

Hand levers or optional Selectable Joystick Controls (SJC)

Foot pedals or optional Selectable Joystick Controls (SJC)


Proportional switch on hand levers or optional Selectable

Infinitely variable tandem hydrostatic piston pumps, driving

Electrically activated proportional front auxiliary hydraulics

Auxiliary hydraulics: variable flow/maximum flow

#### Dimensions



| (A) | 5707.0 11111 | (J) | 2300.0 mm |
|-----|--------------|-----|-----------|
| (B) | 1972.0 mm    | (K) | 467.0 mm  |
| (C) | 24.2°        | (L) | 42.0°     |
| (D) | 185.0 mm     | (M) | 97.0°     |
| (E) | 1082.0 mm    | (N) | 1727.0 mm |
| (F) | 2657.0 mm    | (0) | 2032.0 mm |
| (G) | 3378.0 mm    | (P) | 1374.0 mm |
| (H) | 30.0°        | (Q) | 1643.0 mm |
| (I) | 2205.0 mm    |     |           |

### Attachments

(1)

Angle broom Pallet fork Auger Planer Backhoe Rock bucket Bale fork Scarifier Blades — box, dozer, snow, Scraper snow v-blade Seeder Breaker, hydraulic Brush saw Snowblower Brushcat<sup>™</sup> rotary cutter Sod laver Bucket adapter Buckets Spreader Chipper Combination bucket Steel tracks Concrete mixer Sweeper Diager Drop hammer Tiller Dumping hopper Tilt-Tatch™ Flail cutter Tree spade Grader Grapples - farm / utility, Trencher industrial, root Utility fork I and plane Utility frame Landscape rake Laser equipment Water kit Mower Packer wheel

Snow pusher Soil conditioner Stabilizer, rear Three-point hitch adapter Trench compactor Vibratory roller Whisker broom



Bobcat is a Doosan company. Doosan is a global leader in construction equipment, power and water solutions, engines, and engineering proudly serving customers and communities for more than a century. J Bobcat and the Bobcat logo are registered trademarks of Bobcat Company in the United States and various other countries. ©2020 Bobcat Company. All rights reserved.



Doosan Bobcat Korea Co., Ltd. www.bobcat.com