

SKID-STEER LOADER **S630**

Operating Weight 3496 kg
Engine Power 55.4 kW
Rated Operating Capacity 1040 kg



Pe	٦r	fη	rr	n	ar	۱c	ρ

Tipping load (ISO 14397-1)	2079 kg
Rated operating capacity (ISO 14397-1)	1040 kg
Pump capacity	87.1 L/min
Pump capacity (with high flow-option)	115.5 L/min
System relief at quick couplers	23.8-24.5 MPa
Max. travel speed (high range-option)	19.8 km/h
Max. travel speed (low range)	11.4 km/h

Engine

Make/Model	Kubota/V3307 (iT4)
Fuel	Diesel
Cooling	Liquid
Power at 2400 RPM (SAE J1995 Gross)	55.4 kW (74.3 HP)
Torque at 1600 RPM (SAE J1995 Gross)	264.4 Nm
Number of cylinders	4
Displacement	3331 cm ³
Fuel tank	90.51

Weights

Operating weight	3496 kg
Shipping weight without bucket	3244 kg

Controls

Vehicle steering	Direction and speed controlled by two hand levers
Loader hydraulics tilt and lift	Separate foot pedals or Selectable Joystick Control (SJC)
Front auxiliary (standard)	Electrical switch on right-hand steering lever

Tront auxiliary (standard)	Licetical switch on right-hand steering level
Drive System	
Transmission	Infinitely variable tandem hydrostatic piston pumps, driving

Standard Features

Automatically activated glow plugs
Auxiliary hydraulics: variable flow/maximum flow

Bob-Tach™ frame

Bobcat Interlock Control System (BICS) Operator cab1

Electrically activated proportional front auxiliary hydraulics

Engine/hydraulics system shutdown

Manual

1. Roll Over Protective Structure (ROPS) - meets requirements of SAE-J1040 and ISO 3471; Falling Object Protective Structure (FOPS) - meets requirements of SAE-J1043 and ISO 3449, Level I

Options

2 speed High-flow hydraulics Deluxe instrument panel

Deluxe pressurized cab with heating

Air conditioning Power Bob-Tach™

33x15.5-16.5, 12-ply, Super flotation tyres 12x16.5, 12-ply, Heavy duty tyres, offset rims

12x16.5, 12-ply, Severe duty tyres High-back adjustable suspension seat

Selectable Joystick Controls (SJC) Air ride seat with 2 point seat belt Air ride seat with 3 point seat belt

two fully reversing hydrostatic motors

Lift arm support

Parking brake

Back-up alarm

Seat belt

Seat bar

Work lights, front and rear

12x16.5, 12-ply, Heavy duty tyres

Turbo-charger with approved spark arrestor

Beacon


Engine block heater Fire extinguisher

Strobe

Deluxe operator cab with windows

Hydraulic bucket positioning(including ON/OFF switch)

Dimensions



(A)	3950.0 mm	(J)	3073.0 mm
(B)	2065.0 mm	(K)	544.0 mm
(C)	25.0°	(L)	42.4°
(D)	207.0 mm	(M)	97.0°
(E)	1150.0 mm	(N)	1880.0 mm
(F)	2754.0 mm	(0)	2119.0 mm
(G)	3474.0 mm	(P)	1507.0 mm
(H)	30.0°	(Q)	1832.0 mm
(l)	2367.0 mm		

Attachments

Angle broom Rear stabilizers Rotary cutter (Brushcat™) Auger Backhoe Scarifier Scraper Bale fork Bob-Tach™ backhoe Seeder Box blade Silt fence installer Snow blade Breaker, hydraulic Snow pusher Brush saw Bucket adapter Snow v-blade **Buckets** Snowblower Chipper Sod laver Combination bucket Soil conditioner Concrete mixer Spreader Concrete pump Steel tracks Digger Stump grinder

Dozer blade Drop hammer **Dumping hopper** Flail cutter Forks, utility Grader

Grapple; industrial, root Landplane Landscape rake

Mower Packer wheel Pallet fork

Planer

Sweeper

Three-point hitch adapter

Tiller Tilt-Tatch™ Tree spade Trench compactor Trencher Utility frame Vibratory roller Water kit Wheel saw X-change™ frame



Doosan is a global leader in construction equipment, power and water solutions, engines, and engineering Doubsil is a global electer in conscioución equipment, power and water solutions, regimes, regimes proudly serving customers and communities for more than a century. I Bobcat and the Bobcat logo are registered trademarks of Bobcat Company in the United States and various other countries.

©2020 Bobcat Company. All rights reserved.





Doosan Bobcat Korea Co., Ltd. www.bobcat.com